



# D04CJ-G

**Tier 4 Final**  
**54.5kW @ 1800 rpm**

## SPECIFICATIONS

Model	<b>D04CJ-G</b>
Type	4 cycle water-cooled, cylinder in line
Bore X Stroke (mm)	86mm x 95mm
Cylinder Arrangement	1 - 3 - 4 - 2
Total Displacement	2.207
Combustion System	direct injection
Dry Weight- kg/lbs. (w/o DFP)	260kg
Starting System	Electric
Fuel Oil	Diesel

## POWER RATING

Constant	54.5kW/1800rpm
----------	----------------

# D04CJ-G

## CONSTRUCTION

Ribbed thin-wall cast iron crankcase for added strength and durability  
Internal crankcase breather for reduced emissions  
Extra large bearing surfaces for low bearing loads and long life

## EMISSION CONTROL SYSTEM

DOC

## LUBRICATION

Designed to run at 20° degrees of inclination and includes a full flow spin-on cartridge filter  
Forced circulation by trochoid gear pump  
Oil Capacity: D04CJ : 7.7 ltr

## COOLING

Forced circulation by centrifugal pump  
Cooling packages available for ambient temperatures up to 108° F (42° C)  
Cooling Fan (Std. Eqt.)

## FUEL & COMBUSTION SYSTEMS

Bosch style common rail fuel system with ECU  
Direct injection combustion system for low noise and emissions  
Cylinder head is a pre-chamber design to increase efficiency of combustion

## ELECTRIC SYSTEM

Starter: 12V, 2.0kW  
Alternator: 12V, 50 amp with integral voltage regulator  
Glow Plugs: 12V  
High water temperature and low oil pressure switches  
Stop Solenoid: 12V integrated ETR stop solenoid eliminates external linkage

## MOUNTING

Standard crankcase side mounting pads for flexible mounting arrangements  
Rear engine support available from side mounting pads on SAE #4 housing

## DRIVES

SAE 4 flywheel housing and 7.5 in SAE flywheel  
Rotation direction: counter-clockwise, facing the flywheel end