



6.75LTA OIL & GAS

160 HP @ 1800 rpm – NG



FEATURES

Engine & Block

- Cast Iron Block
- One-piece forged crankshaft
- Separate cast iron cylinder heads and wet cylinder liners
- Forged Connecting Rod

Cooling System

- Radiator and hoses supplied separately
- Thermostatically-controlled system with belt driven
- Water pump and Pusher/Puller fan

Lubrication System

- Flat bottom high capacity oil pan (27 L)
- Cartridge oil filter
- High capacity gear driven lube oil pump

Engine Control System

- Proven ECM, Fuel System and Engine Control
- Engine Protection
- CANBUS J1939 Standard Interface
- Telematics Compatibility

Air Intake & Exhaust System

- Rear Mounted, Replaceable Dry Air Cleaner
- Air Cleaner Restriction Indicator

Electrical System

- 12V electric starter motors
- Optional low voltage battery charging alternator

Flywheel & Housing

- SAE 1/SAE 3 flywheel housing and 11.5/14" flywheel

Weichai America Corp.
 3100 Golf Road
 Rolling Meadows, IL 60008
 Phone: 1-847-725-0300
www.weichaiamerica.com

6.75-LITER ENGINE DATA

Model Number	WP06GTA
Bore & Stroke	4.13 in x 5.12 in (105 mm x 130 mm)
Displacement	412 cid (6,750 cc)
Cylinders	6
Compression ratio	9.8:1
Governor Method	ECM
Fuel Type	Natural Gas / Propane
Aspiration	TA
Emission Standard	EPA Certified
Dry Weight	1,499 lb (680 kg)

POWER RATINGS (PRIME)

	NATURAL GAS		PROPANE	
	kW	HP	kW	HP
1800 RPM	120	160	99	132

